



VSV Remote Monitoring

Product Description

- The Variable Stator Vane (VSV) is part of the High Pressure Compressor (HPC) assembly and thus difficult to access.
- A Linear Variable Differential Transducer (LVDT) system can be installed allowing remote monitoring of Variable Stator Vanes (VSV) positions.
- The LVDT will be mounted on the Compressor Front Frame (CFF) at approximately the 9 o'clock position.
- LVDT is mechanically connected to the VSV union ring by a pin and a clevis arrangement.
- Union ring movement will send a signal back to the operator through the LVDT.
- **Installation will include:**
 - LVDT transducer and hardware.
 - Remote signal conditioner and hardware.
 - Cable between signal conditioner and LVDT.
 - Modified control system and HMI screen software.

Customer Value

- VSV is present to maximize efficiency over a wide range of air speeds.
- Proper monitoring of VSV position with LVDT allows the VSV to function more efficiently.
- LVDT position allows remote monitoring and accurate position of VSV to be known at all times.
- LVDT signal can be used for data or alarm processing.

Applicable Units:

LM6000		LM2500	✓
LMS100		LM5000	
LM1600		TM2500	

GE's global service network provides life cycle support for more than 3,500 aeroderivative gas turbines worldwide to help you meet your business challenges and success metrics – anywhere and anytime. Our global service network connects with you locally for rapid response to your service needs.

www.powergen.gepower.com

The GE brand and logo are trademarks of the General Electric Company.
 © 2015 General Electric Company. Information provided is subject to change without notice.
 All values are design or typical values when measured under laboratory conditions.

GEA32091A (09/2015)